

EFFICIENCY COMES STANDARD

We know harvest is all about timing. Make the most of your field time with a LOCKWOOD® Windrower. Operator-friendly controls and adaptable hydraulics mean you can maximize your efficiency during harvest.



CAN bus system with user-friendly joystick control option.



Updated control screen with better visibility and functionality.

656 Windrower with Dual Discharge





- ☺ Patented telescoping rear cross feature allows for right or left discharge simply by pressing a switch.
- ☺ Larger tires for improved flotation. (Standard on 656 model, optional on 654)
- ☺ Adjustable rear lift allows operator to raise or lower the rear of the machine to accommodate changing conditions.
- ☺ Pressure-sensing support wheels allow for better depth control. (656 only)

- ☺ Staggered secondary available.
- ☺ Hydraulic adjustable hump in primary. (654 only)
- ☺ Single right or left discharge available. (654 only)
- ☺ Tri-discharge capabilities available. (656 only)
- ☺ Improved visibility for product flow.
- ☺ Dual rear cross available on both 654 and 656.



*Patented telescoping rear cross standard on 656 and 654.
Not available on dual- and tri-discharge. Shown here on 656.*

MODEL	654	656
NUMBER OF ROWS	4	6
ROW SPACING	32" - 38"	34" - 38"
DIGGING SPEED	2 - 6 mph	2 - 5 mph
HEADLAND REQUIRED	14' - 18'	20'
EST. HP (MIN)	150	150 - 180
BASE MACHINE (LBS)	18,500 - 22,000	22,000